

Remote Audible / Visual Alarm Annunciator In NEMA 4X (IP56) Enclosure



RA100



RA100-NS

Applications

The RA100 series Remote Annunciator is used in applications where it is desired to have access to audible and optional visual alarms from an on-sight location remote to the TMS tank management console. The RA100 replicates critical alarm warnings, and is typically used in applications where both operational personnel in the active service area and supervisory personnel in a remote office require immediate warning of critical alarms, or where critical alarm warnings are required at both on-sight indoor and outdoor locations. The RA100 is available with strobe and siren, model RA100, or siren only, model RA100-NS.

Physical

- Dimensions (W x H x D): 4.1" x 4.1" x 4.2" (104 mm x 104 mm x 107 mm) (w/ Strobe and Siren)
 4.1" x 4.1" x 2.75" (104 mm x 104 mm x 70 mm) (w/ Siren only)
- Weight: 1.75 lb (0.8 kg) (w/ Strobe and Siren)
 1.6 lb (0.7 kg) (w/ Siren only)
- Operating Temperature: -31 °F to 150 °F (-35 °C to 66 °C)
- Humidity: 100%, Non-condensing
- Enclosure Rating: NEMA 4X (IP56)
- Power Requirements: 96 to 132 VAC, 60Hz
- Audible Alarm: 110dba at 3 feet (1 m)
- Visual Alarm: 15 candela

Note: Specifications subject to change without notice. 04-01-2013