

Low Cost, Single-Tank Gauging System w/Temperature Control and Secondary Containment Leak Detection for Non-Flammable Liquids



Console

- Dimensions (W x H x D): 10.2" x 6.3" x 4.0" (259 mm x 160 mm x 102 mm)
- Weight: 6 lb (2.7 kg)
- Operating Temperature: -40 °F to 160 °F (-40 °C to 70 °C)
- Humidity: 95% Non-condensing
- Enclosure Rating: NEMA 4X (IP56) (Epoxy Powder-Coated Alloy Enclosure)
- Power Requirements: 115/230 VAC ±15% Switchable, 50-60 Hz, 10 W Max.
- Memory: Configuration / Setup Data – EEPROM, 50 year data retention, no batteries
Log Reports and Real-Time Clock – Lithium Battery-Backed RAM, 5-10 year data retention
- Audible Alarm: 100 db
- Display: 9-Character, Super Bright LED Data Display, Readable from 25' (7.6 m)
Ultra-High Intensity Alarm LEDS, Visible from 75' (22.9 m)
- Display Data: Gross Volume, Net Volume (Temperature Corrected), % Volume, Ullage, Product Level, Product Temperature
- Communications: RS-232 Included Standard, RJ-13 Jack
Internal, Secured Modem, Network Interface or ModBus Optional
- Probe / Sensor Capacities: 1 Magnetostrictive Probe – MP55x or MP56x Series
2 Leak/Point-Level Sensors, Supervised Wiring Ready
- I / O, Non-Haz.: Standard: 4 Relays, 1 Form A, Rated 5A @120/240 VAC, w/ 2 Opto-Isolated Inputs
No Expansion
- Alarms: High-High, High, Low, Temperature and Secondary Containment Leak
- Relay Controls: Product - Critical High, High-High, High, Low, Low-Low, Critical Low
Temperature - High-High, High, Low, Low-Low
Secondary Containment Leak Sensor Input
Non-Hazardous Contact Closure Input

Probe

- Technology: Magnetostrictive, Single-Float, w/ reflection resolution doubling
- Accuracy (Minimum):

MP55xS:	Product Level: 0.001" (0.025 mm)	MP56x:	Product Level: 0.01" (0.25 mm)
	Temperature: 0.1 °F (0.06 °C)		Temperature: 0.1 °F (0.06 °C)
- Materials: Shaft: 316 SS Rigid, PVDF Flexible
Float: 316 SS or Buna-N
- Mounting: Inventory Only: 2" minimum riser (4" preferred) or direct bushing/flange mount
- Temperature Sensing: Single sensor standard. Five sensor array available
- Location Approval: Ordinary
- Operating Temperature: -40 °F to 175 °F (-40 °C to 80 °C)
- Operating Pressure: 150 PSIG (1034 kPa) 316SS, 50 PSIG (345 kPa) PVDF
- Field Wiring: 22AWG, 3-Conductor w/ shield and drain wire
Belden 6501FE or equiv., maximum length 50' (15.2 m)
- Models: MP55xS Series rigid SS max. length 24' (7.3 m)
MP56x Series flex. PVDF max. length 70' (21.3 m)

Sensors

- ES825-400FL Electronic, Discriminating - Containment, Manway and Piping Sumps, Dispenser Pan, Dry Annular
- ES825-300FL Electronic, Non-Discriminating - Containment, Manway and Piping Sumps, Dispenser Pan, Dry Annular
- LS600LD Float, Containment, Manway and Piping Sumps, Dispenser Pan
- LS600xx Multi-Float, High / Low Level and Pump Control
- RSU800 Float, Wet Annular / Reservoir
- LS610 Float, Dry Annular
- HS100ND Polymer – Dry Containment, 1' (305 mm) or 2' (610 mm) length

Most sensors are available with Fault-Detect Supervised sensor and wiring option. Add "FL" Suffix to Model Number