


## Remote Audible/Visual Alarm Annunciator with NEMA 4X (IP66) Enclosure



RA105S



RA105HS



RS2

### Applications

The RA105 series Remote Annunciator is used in applications where it is desired to have access to visual and optional audible alarms from an on-sight location remote to any TMS series Tank Management System or LC series Alarm Panel. The RA105S includes a red flashing beacon with 360° visibility, while the RA105HS adds a high intensity audible alarm horn. The RA105HS in conjunction with the RS-2 Remote TEST/RESET pushbutton assembly is ideal as a remote overfill alarm. The RA105 series comes standard with NEMA 4X-rated enclosure suitable for both indoor and outdoor installation. Note RS-2 option supported by TMS and LC2000 series only.

### Specifications

- Dimensions (W x H x D): 7.5" x 10.75" x 5.25" (190 mm x 273 mm x 133 mm) (w/ Beacon Strobe only)  
7.5" x 10.75" x 5.75" (190 mm x 273 mm x 146 mm) (w/ Beacon Strobe and Horn)  
2.55" x 4.53" x 2.62" (65 mm x 115 mm x 67 mm) (RS2)
- Weight: 3.3 lb (1.5 kg) (w/ Beacon Strobe only)  
3.5 lb (1.6 kg) (w/ Beacon Strobe and Horn)  
0.4 lb (0.2 kg) (RS2)
- Operating Temperature: -31 °F to 150 °F (-35 °C to 66 °C)
- Humidity: 100%, Non-condensing
- Enclosure Rating: NEMA 4X (IP66)
- Power Requirements: 96 to 132 VAC, 60Hz
- Audible Alarm: 110dBa at 3 feet (1M) – Red Lense standard. Consult factory for other colors.
- Visual Alarm: 15 Candela

### Model Numbers

- RA105S-1 RA105 Beacon Strobe only, 115VAC
- RA105HS-1 RA105 Beacon Strobe with Horn, 115VAC
- RA105HSKR-1 RA105 Beacon Strobe with Horn and RS-2, 115VAC

70026 – RA105 Spec Sheet – 2-05-2025

Note: Specifications subject to change without notice.



Pneumercator Company, Inc.  
1785 Expressway Drive North  
Hauppauge, New York 11788

Tel: (631) 293-8450

Fax: (631) 293-8533

<http://www.pneumercator.com>