



Remote Audible/Visual Overfill/Leak Alarm Annunciator In NEMA 4X (IP66) Enclosure (Replaces the RA200)

**RA210****RA200PM****RS2**

Product Description

The RA210 series Remote Annunciator is used in applications where it is desired to have access to audible and visual alarms from an on-sight location remote to the TMS tank management console. The most common application is for overfill notification when used with the RS-2 Remote TEST/RESET pushbutton assembly, providing an operator with the ability to test the RA210 prior to a fill operation, and acknowledge the audible portion of the alarm. The RA210 superbright, multi-directional LED array provides 180° visibility when wall-mounted, but can also be ceiling-mounted or pole-mounted with optional L-bracket for 360° visibility. The RA210 is the direct replacement for the RA200, and operates with same RA200PM Power Module and RS-2 Remote TEST/RESET pushbutton assembly.

Specifications

- Dimensions (W x H x D): 6.50" x 8.00" x 4.40" (165 mm x 203 mm x 112 mm) (RA210)
3.54" x 4.53" x 2.17" (90 mm x 115 mm x 55 mm) (RA200PM)
2.55" x 4.53" x 2.62" (65 mm x 115 mm x 67 mm) (RS2)
- Weight: 2.30 lb (1.0 kg) (RA210)
1.05 lb (0.5 kg) (RA200PM)
0.4 lb (0.2 kg) (RS2)
- Operating Temperature: -40 °F to 150 °F (-40 °C to 66 °C)
- Humidity: 95%, Non-condensing
- Enclosure Rating: NEMA 4X (IP66)
- RA200PM Power Requirements: 115/230 VAC Switchable, 50-60 Hz, 8 W Max.
- RA210 Power Requirements: 20VAC, 50-60 Hz provided by RA200PM (Note one RA200PM can power 2 to 3 RA210s)
- Audible Alarm: 110 dba at 3 feet (1 m)
- Visual Alarm: 75 Candela (Amber)

Model Numbers

- RA210K RA210 with RA200PM
- RA210KR RA210 with RA200PM and RS2

70031 – RA210 Spec Sheet – 7-24-2026
Note: Specifications subject to change without notice.



Pneumercator Company, Inc.
1785 Expressway Drive North
Hauppauge, New York 11788

Tel: (631) 293-8450
Fax: (631) 293-8533
<http://www.pneumercator.com>